

QUA-016, rev.: 00

| PORTALÁMPARAS DE BAQUELITA / BAQUELITE LAMP-HOLDER                                |                                                                                                                                                                                                    |                                                                                     |
|-----------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|  |                                                                                                                   |  |
| 161                                                                               | 162                                                                                                                                                                                                | 163                                                                                 |
| FORMA EXTERNA Y DIMENSIONES /<br>EXTERNAL SHAPE AND DIMENSIONS                    | FORMA/SHAPE<br>161: Liso / Plain<br>162: Roscado / Threaded<br>163. Roscado con tope /<br>Threaded with stop ring.<br><br>DIMENSIONES / DIMENSIONS<br>Ø 39 x 54 mm<br>Ø 40 x 58 mm<br>Ø 40 X 54 mm |                                                                                     |
| DIRECTIVA / DIRECTIVE                                                             | 2014/35/UE<br>REBT 2002 – Reglamento de Baja Tensión/ Spanish Low Voltage Regulations                                                                                                              |                                                                                     |
| CARACTERÍSTICAS ELÉCTRICAS<br>ELECTRICAL CHARACTERISTICS                          | Casquillo / Cap: E-27<br>Intensidad /Current: 4 A<br>Tensión / Voltage: 250 V<br>Frecuencia / Frequency: 50 / 60 Hz                                                                                |                                                                                     |
| MATERIAL                                                                          | Baquelita / Baquelite                                                                                                                                                                              |                                                                                     |
| MÉTODO DE FIJACIÓN /<br>FIXING METHOD                                             | Tuerca/ Nut M10 x 1,0<br>Con tornillo antirotación / with antirotating screw                                                                                                                       |                                                                                     |
| TIPO DE BORNE /<br>TERMINAL TYPE                                                  | Borne con tornillo / Screw-type terminal                                                                                                                                                           |                                                                                     |
| RESISTENCIA DE AISLAMIENTO /<br>ISOLATION RESISTANCE                              | >4 M Ω                                                                                                                                                                                             |                                                                                     |
| RIGIDEZ DIELECTRICA /<br>DIELECTRIC STRENGTH                                      | 1500 V                                                                                                                                                                                             |                                                                                     |
| NORMAS APLICADAS /<br>APPLIED STANDARD                                            | EN 60238                                                                                                                                                                                           |                                                                                     |