

SHERWOOD OAK









Garantie








Garantie

Garantie



Garantie



	Product information Produkt informatie	Produkt Daten Information produit		
	Total thickness Totale dikte	Gesamtstärke Epaisseur totale	EN 428	3,20 mm
	Wearlayer Slijtlaag	Nutzschicht Couche d'usure	EN 429	0,30 mm
	Width Breedte	Breite Largeur	EN 426	2m 3m 4m
	Standard length Standard rollengte	Standard Rollenlänge Longueur standard	EN 426	30m 35m
	Total weight Totaal gewicht	Total Gewicht Poids total		2000 g/m ²
	Classification Classificatie	Klassifizierung Classification	EN 685	23 Domestic heavy 31 Commercial moderate

	Technical information Technische informatie	Technische Daten Information technique		
	Light stability Lichtechtheid	Lichtechtheit Résistance à la lumière	ISO 105-B02	≥ 6
	Dimensional stability Dimensionele stabiliteit	Dimensionsstabilität Stabilité dimensionnelle	EN 434	≤ 0,40%
	Underfloor heating Vloerverwarming	Fussbodenheizung Chauffage par le sol	EN 12667	Suitable Geschikt Geeignet Convenable
	Residual indentation Restindrukking	Eindruckverhalten Poinçonnement	EN 433	≤ 0,35 mm
	Impact sound improvement Contactgeluidsisolatie	Trittschallschutz Isolation acoustique	EN ISO 717/2	ΔLw 19dB
	Reaction to fire Brandklasse	Brandverhalten Indice d'incendie	EN 13501-1	B _{fl} S1
	Slipresistance Slipweerstand	Rutschhemmung Glissance	DIN 51130	

SHERWOOD OAK

	
<p>B.I.G. Floorcoverings Rijksweg 442 8710 - Wielsbeke</p>	
<p>06</p>	
<p>EN 14041:2004 Z-156.603-849 Expanded (cushioned) polyvinyl chloride floor coverings (EN653)</p>	
<p>Reaction to fire : Class Bfl/s1 Slipperiness : R10 Formaldehyde : E1</p>	
<p>EN 653</p>	