



中国认可
检验
INSPECTION
CNAS IB0071



NO.2616110109

SAFETY DATA SHEET

Product Name: Li-ion battery pack HT30S-1508D 7. 2V
2. 0Ah 14. 4Wh

Revision Date: 2016-12-01

Compiler: Liu Linlin

Checker: Dongxuesheng

Approver: Zhangxiaojin



Shanghai Research Institute of Chemical Industry Testing Centre



声 明

Statement

1. 本报告无本实验室公章无效。

The report is invalid if it is not affixed the official seal of the laboratory to it.

2. 复制本报告未重新加盖本实验室公章无效。

Copies of the report without the official seal of the laboratory are invalid.

3. 本报告无编制、审核、批准人签字无效。

The report is invalid without the signatures of compiler, checker and approver.

4. 本报告涂改无效。

The report is invalid if it is blotted out.

5. 未经本实验室书面批准，不得部分复制本报告。

It is forbidden to copy the report partially without the written approval of the laboratory.

6. 送样委托检验结果，仅对所送样品有效。

The conclusion of the consignment test is only valid for the provided sample.

7. 除另有说明，检测检验类别都是指委托分析。

Unless noted otherwise, the test type is consignment test.

地址：上海市云岭东路 345 号

Address: No.345 East Yunling Road, Shanghai

邮政编码(Post Code): 200062

电话(Tel): (021) 52569800

传真(Fax): (021) 52569800-0716

网址 (web site): www.ghs.cn

电子信箱(E-mail): fz@ghs.cn

SUZHOU KINGCLEAN PRECISION MACHINERY CO., LTD.

SAFETY DATA SHEET

Li-ion battery pack HT30S-1508D 7.2V 2.0Ah 14.4Wh

SECTION1 PRODUCT AND COMPANY IDENTIFICATION

Product name: Li-ion battery pack HT30S-1508D 7.2V 2.0Ah 14.4Wh
Company: SUZHOU KINGCLEAN PRECISION MACHINERY CO., LTD.
Address: No. 99, Zhufeng Road, Mudu Town, Wuzhong District, Suzhou, Jiangsu Province, 215009, P. R. China
Email: Safaty-certification@kingclean.com
Fax: /
Emergency Phone: +86-512-69583708
SDS Number: 2616110109
SDS Date: 2016-12-01

SECTION2 HAZARDS IDENTIFICATION

Hazards Identification:

The battery has passed the test items of UN Model Regulations, Manual of Test and Criteria Section UN 38.3.

Emergency Overview:

Caution: Avoid contact and inhalation the electrolyte contained inside the battery.

SECTION3 INFORMATION ON INGREDIENTS

Product name: Li-ion battery pack HT30S-1508D 7.2V 2.0Ah 14.4Wh

Ingredient	Concentration	CAS No.	EC No.
Aluminum Foil	2-10%	7429-90-5	231-072-3
Metal Oxide	20-50%	/	/
Polyvinylidene Fluoride	<5%	24937-79-9	/
Copper Foil	2-10%	7440-50-8	231-159-6
Carbon	10-30%	7440-44-0	231-153-3
Electrolyte	10-20%	/	/
Stainless Steel, Nickel and Inert materials	Remainder	/	/

SECTION4 FIRST-AID MEASURES

Skin Exposure:

If the internal battery materials of an opened battery cell come into contact with the skin, immediately flush with plenty of water.

Eye Exposure:

In case of the internal battery materials in contact with eyes, flush with copious amounts of water for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers. Call a physician.

Inhalation Exposure:

If inhaled the internal materials of battery, remove immediately to fresh air and seek medical attention.

Oral Exposure:

If swallowed the internal materials of battery, do not induce vomiting. Seek immediate medical attention.

SECTION5 FIRE FIGHTING MEASURES

Extinguishing Media:

Suitable: Dry chemical, Sandy soil, Carbon dioxide or appropriate foam.

Firefighting:

Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

Specific hazards: Emit toxic fumes under fire conditions.

SECTION6 ACCIDENTAL RELEASE MEASURES

Procedure of Personal Precaution:

If batteries show signs of leaking, avoid skin or eye contact with the material leaking from the battery. Use chemical resistant rubber gloves and non-flammable absorbent materials for clean up. Mix with inert material (e. g. dry sand, vermiculite) and transfer to sealed container for disposal.

SECTION7 HANDLING AND STORAGE

Handling:

Keep away from ignition sources, heat and flame. Such batteries must be packed in inner packages in such a manner as to effectively prevent short circuits and to prevent movement which could lead to short circuits. Avoid mechanical or electrical abuse. More than a momentary short circuit will generally reduce the battery service life. Avoid reversing battery polarity within the battery assembly. In case of a battery unintentionally be crushed, rubber gloves must be used to handle all battery components. Avoid contact with eyes, skin. Avoid inhalation. No smoking at working site. Materials to Avoid: Strong oxidizing agents, Corrosives.

Storage:

Store in a cool, well-ventilated area. Keep away from ignition sources, heat and flame. Such batteries must be packed in inner packages in such a manner as to effectively prevent short circuits and to prevent movement which could lead to short circuits. Materials to Avoid: Strong oxidizing agents, Corrosives.

SECTION8 EXPOSURE CONTROL/PPE**Engineering Controls:**

Use ventilation equipment if available. Safety shower and eye bath.

Personal Protective Equipment:

Respiratory System: Not necessary under conditions of normal use.

Eyes: Not necessary under conditions of normal use.

Clothing: Wear appropriate protective clothing.

Hand: Safety gloves.

Other Protect:

No smoking, drinking and eating at working site. Wash thoroughly after handling.

SECTION9 PHYSICAL/CHEMICAL PROPERTIES

Appearance: Black plastic film shell

Odor: Odorless

Melting Point/°C: >300°C

Solubility: Partial soluble in water

SECTION10 STABILITY AND REACTIVITY**Stability:**

Stable under normal temperatures and pressures.

Conditions to Avoid:

Avoid exposure to heat and open flame. Avoid mechanical or electrical abuse. Prevent short circuits.

Prevent movement which could lead to short circuits.

Materials to Avoid:

Strong oxidizing agents, Corrosives.

Hazardous Polymerization:

Will not occur.

Hazardous Decomposition Products:

Metal oxides, CO, CO₂.

SECTION11 TOXICOLOGICAL INFORMATION**Toxicity Data:**

Not available.

Irritation Data:

The internal battery materials may cause irritation to eyes and skin.

SECTION12 ECOLOGICAL INFORMATION

No data available.

SECTION13 DISPOSAL CONSIDERATION**Appropriate Method of Disposal of Substance:**

Lithium batteries are best disposed of as a non-hazardous waste when fully or mostly discharged. Contact a licensed professional waste disposal service to dispose of large quantities materials.

SECTION14 TRANSPORT INFORMATION

**Lithium battery
contained in the
equipment during
transport:**

Shipping Name: not relevant

Hazard Class: not relevant

UN Number: not relevant

Packing Group: not relevant.

The product shall meet the General Requirements and section II of Packaging Instruction 967 (IATA DGR).

The product is not restricted to IMO IMDG Code according to special provision 188.

SECTION15 REGULATORY INFORMATION

ICAO:

1. Unless be exempted according to ICAO TI, the lithium ion cell/batteries (UN 3480, PI 965) and lithium metal cell/batteries (UN 3090, PI 968) are forbidden for carriage on passenger aircraft.
2. Unless be approved according to ICAO TI, Lithium ion cells/batteries (UN 3480, PI 965) must be offered for transport at a state of charge (SoC) not exceeding 30% of their rated design capacity.
3. A shipper is not permitted to offer for transport more than one (1) package prepared according to Section II of PI 965 and PI 968 in any single consignment. Not more than one (1) package prepared in accordance with Section II of PI 965 and PI 968 may be placed into an overpack.
4. Packages prepared according to Section II of PI 965 and PI 968 must be offered to the operator separately from other cargo and must not be loaded into a unit load device (ULD) before being offered to the operator.

SECTION16 OTHER INFORMATION

Date:

2016-12-01

Department:

Shanghai Research Institute of Chemical Industry Testing Centre
Tel (Fax) :8621-52815377/52800971/52807275/52811034/52569800

Revision:


0

Other Information:

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. We make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of the information for their particular purposes. In no way shall we be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising from using the above information.



研究院



上海化工研究院检测中心
(15)