

Multiple socket outlet, 6-fold, with SP



- 6 diagonally placed, protected sockets
- discharge current max. 12,000 A
- control display shows functioning
- protective sections: N/PE, L/PE
- class of requirement EN 61643-11; type 3
- dimensions (WxHxD): approx. 340 x 60 x 40 mm

■ with child protection

■ with 2-pole, illuminated control switch

■ with surge protection for all sockets

■ H05VV-F 3G1.5 mm² cable

■ for indoor use

■ 16 A, 230 V~, 50 Hz, max. 3500 W, Uoc 3 kV, Up 1.8 kV

Art.no.

00125101

Description

1.4 m, white

Common data

type of packing	Beutel m. Reiter
garanty	36 month
customs tariff number	85444290900
EAN-Code	4006341605528

Quantities

PU	10	piece
number of PU per export board	0	piece
number of products per pallet	0	piece
number of PU per board layer	0	piece
number of board layers per pallet	0	piece
number of PU per pallet	0	piece

Weights

weight product	424 g
weight packing	0 g
weight packed product	434 g
weight PU	4,869 kg
weight export board	0 kg
weight pallet	0 kg

Dimensions

dim product	35,2x11,2x5,8 cm
dim. packing	36,9x13,8x6,3 cm
dim. PU board	39,4x29,3x18,5 cm
volume PU	21,357 dm ³
Dim. export board	cm
height of pallet	0 cm