



BOSCH

Innovación para tu vida



Bosch Modelo CLIMATE 3000i			2,6 kw	3,5 kw	5,3 kw	7 kw
			9K	12K	18K	24K
REFERENCIA SET			7733701735	7733701736	7733701737	7733701738
EAN SET			4062321345556	4062321345563	4062321345570	4062321345587
Alimentación		Ph-V-Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz
Frío	Capacidad (Potencia)	Btu/h	9000 (3500~11000)	12000 (4700~14700)	18000(7200~20130)	24000(11570-28000)
		kW/h	2,6 (1,0~3,2)	3,5 (1,4~4,3)	5,3 (2,1~5,9)	7,0 (3,4~8,2)
		kcal/h	2268 (882~2772)	3024 (1184~3704)	4536 (1814~5073)	6048 (2916~7056)
	Consumo	W	733 (80~1100)	1096 (120~1650)	1550(560~2050)	2402(420-3200)
Calor	Capacidad (Potencia)	Btu/h	10000 (2800~11500)	13000 (3650~14950)	19000(5300~19960)	25000(10580-28000)
		kW/h	2,9 (0,8~3,4)	3,8 (1,1~4,4)	5,6 (1,6~5,8)	7,3 (3,1~8,2)
		kcal/h	2520 (706~2898)	3276 (920~3767)	4788 (1336~5030)	6300 (2666~7056)
	Consumo	W	771 (70~990)	1027 (110~1480)	1750(780~2000)	2130(300-3100)
Frío (estaciona	Pdesignnc	kW	2,8	3,6	5	7,0
	SEER	W/W	7,4	7,0	7,0	6,4
	Etiqueta energética		A++	A++	A++	A++
Calor estacional (Clima medio)	Pdesignnh	kW	2,5	2,5	4,2	4,9
	SCOP	W/W	4,1	4,2	4,0	4,0
	Entiqueta energética		A+	A+	A+	A+
Calor estacional (Clima cálido)	Pdesignnh	kW	2,5	2,5	4,5	5,3
	SCOP	W/W	5,2	5,5	5,1	5,1
	Entiqueta energética		A+++	A+++	A+++	A+++
Caudal de aire interior (Bajo/Medio/Alto)		m3/h	330/460/520	350/400/530	500/600/800	610/770/1090
Nivel de presión sonora interior (Si/Bajo/Medio/Alto)		dB(A)	20/22/32/37	21/22/32/37	20/31/37/41	21/34.5/37/46
Unidad Interior	Dimensiones (Ancho*Profundo*Alto)	mm	729x200x292	802x200x295	971x228x321	1082x234x337
	Peso Neto/Bruto	Kg	8/10.5	8.7/11.5	11.2/14.6	13.6/17.3
Caudal de aire exterior		m3/h	1850	1850	2100	3500
Nivel de presión sonora exterior		dB(A)	55,5	55,0	57	60
Unidad Exterior	Dimensiones (Ancho*Profundo*Alto)	mm	720x270x495	720x270x495	805x330x554	890x342x673
	Peso Neto/Bruto	Kg	23.5/25.4	23.7/25.5	33.5/36.1	43.9/46.9
Refrigerante	Tipo	-	R32	R32	R32	R32
	GWP	-	675	675	675	675
	Cantidad carga	Kg	0,6	0,65	1,1	1,45
	Equivalente de CO2	t	0,405	0,439	0,743	0,979
Tubería refrigerante	Líquido / Gas	mm	6.35mm/9.52mm	6.35mm/9.52mm	6.35mm /12.7mm	9.52mm/15.9mm
	Máx. Longitud	m	25	25	30	50
	Máx. Vertical	m	10	10	20	25
	Distancia estándar	m	5	5	5	5
	Carga adicional	g/m	12	12	12	24
	Exterior (frío)		-15~50	-15~50	-15~50	-15~50
	Exterior (calor)		-15~24	-15~24	-15~24	-15~24
Área recomendada (Refrigeración estandar)		m2	12~18	16~23	24-35	32-47